

WASTEWATER/GREYWATER PUMP STATIONS

CUBE

DESCRIPTION

- Smaller sized self contained above-ground wastewater pump out unit, for situations where gravity is not feasible
- Units are usually installed below sink or basin unit to accept gravity waste pipe inlets

NB: Separate carbon vent available if required, otherwise units require venting. Hunter valves are not suitable

CONSTRUCTION/FEATURES

- Polyethylene Sealed Tank c/w bolted PE Sealed lid
- Non-corrosive and long lasting tank
- Semi-Compact - more suited for domestic and light commercial applications where less space is available
- Simple installation - all internal plumbing done
- 3 standard pump options - Custom units available with larger pumps
- 2 year pump warranty



Tank size: 410mm L x 300mm W x 400mm H
Tank capacity: 43 Litres

APPLICATIONS

- Kitchen Sinks/Kitchenettes/Bakeries
- Laundry Tubs/Washing Machines
- Cleaners Sinks/Wash Rooms
- Restaurants/Cafes/Lunch Bars
- Doctors/Dentists/Clinics
- Surgeries/Hospitals/Medical Centres
- Office Blocks/High rise buildings
- General domestic and light commercial

Model	Motor size	Voltage	Solids Passage	Outlet size
CUBE - STD (Standard)	0.22kW	230 V	10mm	32mm
CUBE - PLUS (Medium)	0.55kW	230 V	10mm	32mm
CUBE - VX (Vortex)	0.55kW	230 V	25mm	32mm

High Level Alarm available if required. Refer page 120
Solenoid valves available if required. Refer page 106

HYDRAULIC DATA

