

### SEWAGE & WASTEWATER LIFTING STATIONS

ABS - SANIMAT

#### DESCRIPTION

- Above-ground compact self-contained sanitary pump-out units for pumping of either raw sewage/greywater
- Units are either installed in recess/cavity or basement below the level of the fixtures
- Especially designed for tight spaces where holding tanks are not feasible
- Single or Dual pump options available in both single and three phase
- ABS, Grundfos, Sanimaster brands available

#### CONSTRUCTION/FEATURES

- Robust, compact, polyethylene tanks
- Easily transported and fitted up on site
- Powerful Grinder or Vortex Pump options
- Multiple inlet port options available
- Cast iron motor housings and impeller
- Integrated ball type NRV included
- Large range of flows and heads available
- 2 year warranty

#### APPLICATIONS

- Commercial Sanitary Fixtures
- Bathroom/Basement Ensuites
- Toilets/Showers/Wash Hand Basins/Vanity Units
- Laundry Fixtures - Tubs & Washing Machines
- Kitchen Fixtures/Bars/Restaurants/Cafes

Model	Motor size	Voltage	Outlet size
1000 W (single)	1.3 kW	230 V	80/100mm
1000 D (single)	1.4 kW	400V	
1000 D/HD (single)	2.2 kW	400V	
1002 D (Dual)	1.7 kW	400V	80/100mm
1002 D/HD (Dual)	2.2 kW		
2002 D/HD (Dual)	2.2 kW	400V	80/100mm
2002 D/XD (Dual)	3 kW		

#### Code

1000 Series Tank = 70 Litre Capacity  
 1002 Series Tank = 140 Litre Capacity  
 2002 Series Tank = 320 Litre Capacity

\*Solenoid valves available if required - Refer pages 106 & 120.



ABS SANIMAT 2002

#### TYPICAL INSTALLATION

